



exclusive appearance
 VESA mounting
 different touch options

With the sleek elegant design and the plastic and aluminum combined housing, Booster is a state of the art POS monitor for all your POS needs. Whether operating in humid hot or dusty areas, Booster can function competently under any environment circumstances. This monitor is equipped with an industrial grade LCD panel which provides high quality and durability with a long lifecycle.



Touch Monitor MRP/MIP/MCP-255 Booster



1. Adjustable panel



3. Optional fingerprint reader



2. Aluminium stand for extra stabilisation



4. Optional IButton reader



MRP/MIP/MCP-255 Booster



Model Name	MRP-255	MIP-255	MCP-255
Housing			
Bezel	Plastic		
Stand	Aluminium		
VESA Mounting	100 x 100 VESA Standard		
LCD/Touch Panel			
LCD Size	15" TFT LCD		
LCD Brightness	250 cd/m2 standard upgradeable to 350 cd/m2		
Maximal Resolution	1024 x 768 pixels		
Support Colour	16.7M colors (6-bit with A-FRC)		
Response Time	8 msec		
Viewing Angle	70°/70° (L/R) 65°/60° (U/D)		
Touch Screen Type	ELO 5-wire resistive touch	Infrared touch	ELO capacitive touch
Tilt Angle	0° C ~ 70° C		
Touch Interface	USB or Serial		
I/O Connectivity			
PS/2	1 x Keyboard for Magnetic Strip Card Reader		
Video Port	1 x VGA (D-Sub 15-pin)		
DC-in Port	DC + 12V/4 A Input		
Power			
Power Supply	external 48W AC		
Environment			
EMC & Safety	FCC Class A / CE Marking / UL / RoHS		
Operating Temperature	0° C ~ 40° C		
Dust & Water Proof	NEMA 3 / IP54		
Options			
Magnetic Card Reader	3 Tracks		
Dallas Key Reader	2-in-1 (MSR + iButton)		
Fingerprint Reader	2-in-1 (MSR +Finger Print)		
Customer Display	VFD / LCD pole display		
Dimension (W x D x H)			
	377 x 231 x 344 mm		
Weight			
	6.5 kg		
Colour			
	Black		

V01/12

