

## Internal Peel & Rewind

High-speed industrial printing



### Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

### Front loading rewriter

The clever and unique CL-S700R includes an internal rewriter that is simplicity itself to use. The front door drops down and the liner or labels are loaded.

### Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

## CL-S700R-CL-S703R

Label, Industrial

### Applications

- Courier
- Logistic / Transport
- Manufacturing
- Retail
- Warehousing



High performance with easy access

# CITIZEN

## Specifications

Model	CL-S700R-CL-S703R
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi, 300 dpi
Print Speed (maximum)	8 inches per second (200 mm/s), 10 inches per second (254 mm/s), 7 inches per second (175mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 to 5 inches (25.4 to 118.1 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 32 inches (6.35 to 812.8 mm)
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT)
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 4-line back-lit graphic LCD
Emulations (Languages)	Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400

## CL-S700R-CL-S703R

### Label, Industrial

#### Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- Low space requirement - integrated power supply enables clean work station
- Recyclable packaging



Ingeniously designed for easy operation and reliability

# CITIZEN

## CL-S700R-CL-S703R

**Label, Industrial**

<b>Model</b>	<b>CL-S700R-CL-S703R</b>
<b>Drivers and software</b>	Free-of-charge on CD with printer, including support for various platforms
<b>Flash (Non-Volatile Memory)</b>	4 MB total, 1 MB available for user
<b>Size (W x D x H) and Weight</b>	255 x 490 x 385 mm, 17.6 Kg, 255 x 490 x 265 mm, 13.3 Kg, 255 x 490 x 265 mm, 12.5Kg
<b>Warranty</b>	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0